

1140



The Tally Dascom 1140, is a 9 pin, 80 column serial dot matrix printer with a USB interface as standard. Compact in size, the 1140 is perfect for industrial environments and front and back office applications where space is limited.

With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

Highlights at a glance:

- Compact 9-pin narrow carriage printer
- Up to 400 characters per second
- Ideal for front and back office applications
- Variety of interfaces
- Long life ribbon
- Small footprint

In addition to these applications, the 1140 is also well suited to measurement and control systems. Among the lowest priced matrix printers available today, the 1140 also offers a long life ribbon giving this printer very low running costs.

For draft printing it's considerably less expensive operating costs make it a viable alternative to low end inkjet printers.

Configurations Available:

Part Number	Description
28830504	1140 Printer, 9 pin, 80 Col - 110/240v, USB
28830510	1140 Printer, 9 pin, 80 Col - 110/240v, USB and Parallel
28830511	1140 Printer, 9 pin, 80 Col - 110/240v, USB and Serial
099007	Ribbon, Tally Dascom 1140

1140

Print Speed	400 cps (Fastest Draft); 300 cps (Draft), 75 cps (NLQ) at 10 cpi
Resolution	up to 144 x 240 dpi
Throughput	290 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Print Head Life	400 million strokes
Memory	up to 256 kB
Standard Connectivity	USB 2.0
Optional Connectivity	Parallel IEEE 1284, Serial RS-232C, Ethernet (10/100)
Standard Emulation	IBM ProPrinter 2380 Plus, Epson ESCP/2
Fonts	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Consumables	Ribbon: 9 million characters
Standard Paper Handling	Pushtractor and friction
Optional Paper Handling	Roll holder
Number of Copies	1 original + 4 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	52 - 100 g/m ²
Paper Size	Width: 95 to 267 mm, 9.75 to 10.5 in, Length: 114 to 362 mm, 4.5 to 14.25 in. (Cut sheet); 114 to 558 mm (4.5 to 22.0 in) (Fanfold)
Physical Weight	5 kg, 11 lbs
Physical Size	369 x 283 x 130 mm, 14.5 x 11.1 x 5.1 in., (W x D x H)
Acoustics	57 dB(A)
Power Voltage	100-240 V - 50/60 Hz
Power Consumption	less than 1.2 Watt Sleep Mode
Temperature	+5° to +35° C; 41° to 95° F 10% to 80% humidity
Workload	6,000 pages per month
MTBF	12,000 hours
Drivers	Windows Vista/7/ 8.1 and Server 2008/2012
Cover Set Color	Night Sky Gray (Pantone 432)
Warranty	One year return to depot

Note:

For OCR applications, it is recommended that your readers are tested with sample printouts supplied by Dascom. Paper is a highly variable medium and should be tested prior to purchase.

Dascom Americas

34 Lakeview Court

Verona, VA 24482

Tel: 540-904-0391 or 877-434-1377

Fax: 540-242-7221

www.dascomamericas.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 