

# T2365/T2365 HD



# Tally

The T2365 series printers represent top of the line print speeds, rugged durability and unsurpassed performance under the most extreme conditions.

These work-horse printers guarantee crisp, dark, clear and legible print thanks to the advanced engineering of the 24 pin print head so even in the most challenging operating environment, you can be assured of the best in quality and performance.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

## Rugged Design, High Speed

- Parallel, Ethernet, Serial RS232, and IBM AS400/iSeries Mainframe Ethernet IPDS interfaces
- Full range of automatic features to minimize user intervention and straight through paper path for easy forms loading
- Ideal for OnDemand and Batch applications with zero tear for no wasted forms

The T2365 series printers are well matched to Microsoft Windows applications and are highly compatible with other host operating environments including legacy systems. Fully automated operation, coupled with the 'straight' through paper path, allows ease of use and virtually eliminates errors caused by user intervention.

The US Postal Service Intelligent Mail® Barcode standard will require this capability to take advantage of the best rates available.



### Available configurations:

- T2365 Standard Product
- T2365 2T with additional Rear Tractor
- T2365 HD Heavy Duty version for up to 9-parts
- T2365 2T HD Heavy Duty version with additional Rear

# T2365/T2365 HD

Print Speed	900 cps (HS @ 15 cpi); 700 (HS), 600 cps (Data Print), 200 cps (NLQ @ 10 cpi) 800 cps (HS @ 15 cpi); 640 (HS), 533 cps (Data Print), 180 cps (NLQ @ 10 cpi) HD model
Print Method	Serial Impact
Resolution	Up to 360 x 360 dpi (ESC/P Emulation only)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Throughput	(ECMA 132 @ 10cpi) 605 pages per hour (HD 587 pages per hour)
Printhead Life	750 million strokes per pin (500 million strokes per pin HD model)
Throughput (ECMA 132)	610 pages per hour, 595 pages per hour HD model
Standard Memory	128 kB
Standard Connectivity	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
Optional Connectivity	RS232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS, Serial RS232, adapters, Ethernet IPDS: USB parallel adapter IBM proprinter
Standard Emulation	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP
Optional Emulation	PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564C, ANSI
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractors with paper parking and AGA; Cut sheet front insertion with AGA
Optional Paper Handling	2nd front tractor (user installable); Dual bin automatic sheet feeder, 190 sheets per bin; Face down output bin;
Number of Copies	Up to 6 part forms. (1+1 for rear tractors of 2280-2T)
Paper Type	Continuous forms, cut sheets
Paper Weight	60 – 120 g/m <sup>2</sup>
Paper Size	Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm)
Physical Size (W x D x H)	24.5" x 11" x 17" (622 x 280 x 432 mm)
Physical Weight	42 lbs (Approximately 19 kg)
Power Voltage	120 V or 230 V (auto-switching)
Power Consumption	60 Watt while Printing; 18 Watts while in power save
Workload	Up to 48,000 pages per month
Drivers	Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP
Reliability MTBF	22.500 hours
Temperature	50 °F – 95 °F (+10 °C to +35 °C)
Humidity	20% to 80% RH (not condensing)
Acoustic	55 dB(A)
Warranty	90 days on-site warranty

DASCOM Americas  
34 Lakeview Court  
Verona, Virginia, 24482 . USA.  
Tel: +1 (877) 434-1377  
www.dascomamericas.com  
info.us@dascom.com

**THERMAL PRINTERS**  
**MOBILE PRINTERS**  
**MATRIX PRINTERS**  
**POS PRINTERS**  
**ID PRINTERS**