

LA2610+



The Tally Dascom LA2610+ is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

Highlights at a glance:


- Print speeds up to **683 cps**
- **20,000** pages per month workload
- **136** columns
- **24 pin print head** produces excellent print quality
- **Straight through paper path** for easy forms loading
- **Ethernet, Parallel** and **USB** interfaces standard
- **LC Display** for easy operation
- Includes **DEC PPL2** command set and **MMJ Adapter**

User intervention is kept to a minimum with a suite of features designed to ensure the product runs at optimum reliability and performance.

DEC compatible printers continue to be in demand. These printers are particularly suited to DEC Servers, DEC VAX and Alpha, in VMS and OpenVMS operating environments.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.



Configurations:

- **LA2610+** Standard Product

LA2610+

Print Speed	680 cps (HS-Draft @ 12cpi); 513 cps (Draft), 342 cps (C-Draft), 114 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million dots per wire
Memory	256 kB
Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (IPv4 & IPV6), Serial RS232, DEC MMJ Adapter included
Optional Connectivity	N/A
Standard Emulation	DEC PPL2, IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
Consumable	Ribbon: 15 million characters
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
Optional Paper Handling	Additional push tractor (rear)
Number of Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3.0 to 16.5 in, 76 to 420 mm; Length: 3.0 to 23.6 in, 76 to 599 mm
Physical Weight	23.3 lbs 10.6 kg
Physical Size	23.6 x 10.4 x 7.9 in (W x D x H) 600 x 267 x 200 mm
Acoustic	52 dB(A)
Power Voltage	100 - 240 V wide range auto-sensing
Power Consumption	40 Watt Printing; <2.3 W Sleep Mode
Temperature	+50° to +104° F, +10° to +40° C; 10% to 85% humidity
Workload	20,000 pages per month
MTBF	20,000 hours
Drivers	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008/2012/2016; SAP
Warranty	1 yr. Return To Depot