

Tally DASCOM 1140 Roll Holder Impact Printer



Tally
DASCOM

Based on the proven quality of the Tally Dascom 1140 the roll holder version is specially designed for roll paper applications that can be found on airports, railways and travel agencies.

The support has been designed to be set up by any user. The user just clips while being firmly fixed and connect the equipotential bonding to the printer chassis.

Made of metal, it will easily withstand rough handling by users and can works with roll up to 2

Highlights at a glance:

- Compact 9-pin narrow carriage printer
- Up to 400 characters per second
- Ideal for airport applications
- Solution designed for airport counters
- Roll support clipped and attached to the printer
- Excellent paper holding
- Long life capacity ribbon

kilograms (4.4 lbs). When exchanging the paper roll the axle won't be lost as it is fixed to the mechanism.

No additional footprint required as the roll holder is fixed on the printer. The back of the printer can be positioned at the edge of the desk and the roll media will not be affected. Users will be able to move the printer without worrying about the roll support because it is attached to the printer.

Common Configurations:

28.892.1530 TallyDascom 1140 USB

28.892.1524 TallyDascom 1140 USB, Par

28.892.1525 TallyDascom 1140 USB, Ser

28.892.1526 TallyDascom 1140 USB, Eth

28.892.1527 TallyDascom 1140 USB, BT

28.892.1528 TallyDascom 1140 USB,Wi-Fi

Tally DASCOM 1140 Roll Holder Impact Printer

Print Speed	Fastest Speed: 400 cps Character density 10 / 12 / 15 cpi HS Draft 400 / 360 / 300 cps Draft 300 / 360 / 300 cps NLQ 75 / 90 / 75 cps
Resolution	up to 144 x 240 dpi
Throughput	Up to 290 pages per hour
Character density	10,12,15,17.1,20 cpi
Line density	1.2, 3.4.8 lpi
Print head life	400 million impacts per needle
Memory	Up to 256 Kb
Standard connectivity	USB 2.0
Optional connectivity	Parallel IEEE 1284. Serial RS-232C, Ethernet (10/100)
Emulation	IBM ProPrinter 2380 Plus, Epson ESC P / 2
Fonts / Barcodes	Draft, Quadrato, Courier, HS Draft, OCR-A / B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Paper handling	Roll paper
Number of copies	1 original + 4 copies
Paper type	Continuous paper rolls, multi-part forms Max. roll diameter: 130 mm / 2 kg (5 inches / 4 pounds) Min. core paper roll: 20 mm (0.8 inches)
Paper weight	52 - 100 g/m ² (0.5 - 1.1 lb/ft ²)
Paper size	Width: 75 to 220 mm (2.95 to 8.66 inches)
Weight	5kg (11 lbs)
Size	Width x Depth x Height: 369 x 283 x 130 mm (14.5 x 11.1 x 5.1 inches)
Acoustics	57 dB (A)
Consumption	Average power consumption: 29 W (Test pattern according to ISO / IEC 10561 standard) Less than 1.2 W in sleep mode
Voltage	120/230 V - 50/60 Hz
Humidity, Temperature	10% to 80% RH and + 5 ° to + 35 ° C (41 ° to 95 ° F)
Working capacity	Up to 6,000 pages per month
MTBF	12,000 hours
Drivers	Windows 8/ 8.1/10/11 and Server 2012/2016/2019/2022
Warranty	One year

DASCOM Americas

34 Lakeview Court
Verona, Virginia, 24482 . USA.
Tel: +1 (877) 434-1377
www.dascomamericas.com
info.us@dascom.com

DASCOM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0
Fax: +49 731 2075-100
info@dascom.com
www.dascomeurope.de

DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road
Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507
Fax: +852 2413 6047